International Journal of Creative and Open Research in Engineering and Management
ISSN: 3108-1754 (Online)
Volume 02 Issue 10 October-2026 | Impact Factor: 3.5



Terrian Exploration and Reconnaissance Integrated Rover System

Dr.S.Venkatesan, Muralikrishnan R S, Harshvardhan G K, Sikkandar batcha J, Vignesh Karthick U

1 Professor, Dept. of EEE, K.L.N. College of Engineering, Sivagangai, Tamilnadu, India

2 UG Student, Dept. of EEE, K.L.N. College of Engineering, Sivagangai, Tamilnadu, India

3 UG Student, Dept. of EEE, K.L.N. College of Engineering, Sivagangai, Tamilnadu, India

4 UG Student, Dept. of EEE, K.L.N. College of Engineering, Sivagangai, Tamilnadu, India

5 UG Student, Dept. of EEE, K.L.N. College of Engineering, Sivagangai, Tamilnadu, India Corresponding Author

Email: muralikrishnan2124@email.com

How to Cite this Article:

S, M. R., K, H. G., J, S. B. & U, V. K. (2026). Terrian Exploration and Reconnaissance Integrated Rover System. International Journal of Creative and Open Research in Engineering and Management, 02(04), 1-9. https://doi.org/10.55041/ijcope.v2i10.148

License:

This article is published under the terms of the Creative Commons Attribution 4.0 International License (CC BY 4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author(s) and the source are credited.

© The Author(s). Published by International Journal of Creative and Open Research in Engineering and Management.







https://doi.org/10.55041/ijcope.v2i10.148

Abstract—

Hazardous and inaccessible environments create serious risks for personnel conducting inspection, disaster response and reconnaissance. This paper presents the Terrain Exploration and Reconnaissance Integrated Rover System, a four-wheel-drive mobile platform controlled by an ESP32 microcontroller. The rover integrates ultrasonic and infrared sensors for obstacle and edge detection, a flame sensor for fire detection, an MQ-6 sensor for combustible-gas monitoring, and a DHT11/DHT22 sensor for temperature and humidity measurement. An onboard camera provides visual information, while Wi-Fi enables bidirectional communication between the rover and a phone or laptop. The ESP32 processes sensor readings, controls an L298N motor driver and DC gear motors, and issues audible alerts through a buzzer when selected hazards are detected. The system was assembled and tested for movement commands, obstacle response, flame and gas detection, environmental monitoring, camera operation and wireless data transmission. The reported tests demonstrated that the integrated platform could move under remote command, detect obstacles and report sensor and video information to the operator. The design combines several reconnaissance functions on a compact, modular and relatively low-cost platform, reducing the need for direct human entry into risky areas. Limitations include dependence on wireless range, sensor accuracy and battery capacity, as well as the absence of fully autonomous navigation. Future work may add GPS, autonomous path planning, thermal imaging and a robotic arm

KEYWORDS: ***Mobile rover; ESP32; hazard detection; wireless monitoring; reconnaissance; disaster response*;**



1. INTRODUCTION

This project describes the design and implementation of the **Terrain Exploration and Reconnaissance Integrated Rover System**. It is a four-wheel-drive rover controlled by an **ESP32 microcontroller**. The ESP32 is a dual-core processor with built-in Wi-Fi and Bluetooth, many GPIO pins, analog inputs and PWM outputs, so a single chip performs the sensing, the decision making, the motor control and the wireless communication. This keeps the circuit simple and the cost low, because no separate controller board and no external wireless module are required.

The rover carries a group of sensors on one platform. An ultrasonic sensor and an IR sensor warn the rover of obstacles and edges. A flame sensor detects fire, an MQ-6 sensor detects smoke and combustible gas, and a DHT11/DHT22 sensor measures temperature and humidity. A camera module sends live video of the terrain.

Many of the places where information is needed most urgently are also the places where it is hardest and most dangerous to obtain. After an earthquake, a building collapse or an industrial accident, rescue teams must decide where to go and what to do with very little knowledge of what is inside. There may be fire behind a wall, a build-up of toxic or combustible gas, or a floor that is about to give way. In the same way, inspection of forests, mines, pipelines, chemical plants and rough outdoor ground requires people to travel through difficult terrain, often for long hours and sometimes at serious risk to their health and safety.

Robots are well suited to such work. A mobile robot does not get tired, it can be fitted with sensors that detect things people cannot sense, and if it is damaged it can be replaced, which a human life cannot. For this reason, mobile robots are now widely accepted as part of disaster response, search and rescue, surveillance and industrial inspection. A good reconnaissance robot should move reliably over uneven ground, avoid obstacles, sense hazards in its surroundings, show the operator what it sees and respond to remote commands.

2. LITERATURE REVIEW

Research on robots for hazardous environments grew quickly after real disasters showed how useful small mobile robots can be. Murphy has described the use of rescue robots at the World Trade Center site and has discussed the wider field of disaster robotics.. They also showed that the main difficulties are rough terrain, limited wireless communication and the need to give the operator a clear picture of the scene.

Kleiner, Dorn Hege and Nebel discuss search and rescue robotics in the Springer Handbook of Robotics and describe the main design problems: mobility on uneven ground, sensing of victims and hazards, communication in damaged environments and the human–robot interface. The handbook edited by Siciliano and Khatib gives a broad treatment of robot design, sensing and control. Siegwart, Nourbakhsh and Scaramuzza, and Thrun, Burgard and Fox, explain the fundamentals of mobile robot locomotion, perception, localisation and navigation that form the theoretical basis of any rover.

Yamauchi has proposed frontier-based exploration, in which robots move towards the boundary between known and unknown space to explore an area autonomously. Such techniques are suitable for emergency reconnaissance and indicate a direction for future development of this rover. Quigley and co-workers introduced ROS, an open-source framework that is widely used for building robotic systems, and the National Institute of Standards and Technology (NIST) has published standard test methods that are used to evaluate the performance of response robots.

Wang, Shi and Yan, in the IEEE Internet of Things Journal (2025), study post-disaster data collection and routing using the Internet of Robotic Things. Their work shows how wireless communication and real-time data transmission allow robots to collect disaster information and pass it quickly to those who need it. This supports the use of a wireless, ESP32-based link between the rover and the operator in the present project.

3. METHODOLOGY

The proposed system is a Terrain Exploration and Reconnaissance Integrated Rover designed to explore uneven, hazardous and inaccessible areas remotely. The rover uses an ESP32 microcontroller to control its movement and to




process data from the sensors. Ultrasonic and IR sensors are used for obstacle and terrain detection, while a camera provides real-time visual monitoring.

Environmental sensors detect conditions such as temperature, humidity, smoke, gas and fire. The built-in Wi-Fi of the ESP32 enables remote control and the transmission of sensor and camera data to the operator on a phone or laptop. In this way human exposure to dangerous environments is reduced.

4. WORKING PRINCIPLE

The Terrain Exploration and Reconnaissance Integrated Rover System operates using an ESP32 microcontroller that controls a four-wheel-drive rover. The rover moves forward, backward, left, and right through commands received over Wi-Fi. An L298N motor driver controls the motors according to the microcontroller's instructions. Ultrasonic and infrared sensors help detect obstacles and nearby objects. A flame sensor identifies fire, while an MQ-6 gas sensor detects combustible gases. Temperature and humidity sensors monitor environmental conditions. A camera provides visual information about the surroundings. The collected information supports remote monitoring, exploration, and reconnaissance in hazardous or inaccessible environments.



5. CIRCUIT CONNECTIONS AND DESCRIPTION

The ESP32 microcontroller connects the sensors, L298N motor driver, and buzzer. The ultrasonic and IR sensors detect obstacles, while flame and MQ-6 sensors identify hazards. The DHT sensor monitors temperature and humidity. A lithium-ion battery supplies power through a buck converter. The ESP32 uses Wi-Fi to enable remote rover movement, live video monitoring, and sensor data transmission to a phone or laptop for reconnaissance and environmental monitoring.

Module	Signal	ESP32 pin
L298N	IN1, IN2 (left motors)	GPIO 26, GPIO 27
L298N	IN3, IN4 (right motors)	GPIO 14, GPIO 12
L298N	ENA, ENB (PWM speed)	GPIO 25, GPIO 33
HC-SR04	Trig / Echo	GPIO 5 / GPIO 18
IR sensor	Digital out	GPIO 19
Flame sensor	Digital out	GPIO 21
MQ-6	Analog out	GPIO 34 (ADC1)
DHT11 / DHT22	Data	GPIO 4
Buzzer	Signal	GPIO 23

6. ADVANTAGES OF PROPOSED SYSTEM

The proposed Terrain Exploration and Reconnaissance Integrated Rover System offers several advantages. It reduces human exposure to hazardous environments by enabling remote operation. The ESP32 provides an affordable and compact control solution with built-in Wi-Fi. Multiple sensors detect obstacles, fire, combustible gases, temperature, and humidity. The ultrasonic



and IR sensors support obstacle avoidance, while the camera provides visual monitoring. Real-time sensor data and video can be accessed through a phone or laptop. The four-wheel-drive mechanism improves mobility across different terrains. Its modular design supports future upgrades and makes the system useful for disaster response, industrial inspection, environmental monitoring, and reconnaissance.


7. CONTROL STATERGY

The program runs in a continuous loop, After the pins, the sensors, the camera and the Wi-Fi connection are initialised, the program checks whether the user is authorised. If so, it reads the sensors, checks for obstacles and hazards, executes the command received from the operator and sends the data back. Safety checks come before the operator command, so the rover stops for an obstacle or an edge even if the operator keeps sending a forward command.




8. BLOCK DIAGRAM

Environmental sensors detect conditions such as temperature, humidity, smoke, gas and fire. The built-in Wi-Fi of the ESP32 enables remote control and the transmission of sensor and camera data to the operator on a phone or laptop. In this way human exposure to dangerous environments is reduced.



9. SIMULATION



The circuit is designed and simulated using the Arduino Uno in Cirkit Designer to verify the connections between the motor driver, DC motors, ultrasonic sensor, IR sensor, gas sensor, and other components. The Arduino processes the sensor inputs and controls the motors according to the programmed instructions. A separate output screen is used to display the simulation results, including sensor readings, obstacle detection, and system responses, making it easier to observe and analyse the rover's operation.



10. APPLICATIONS AND USES OF THE ROVER

Because the rover can be switched between modes and carries a general set of sensors, it can be used in many fields.

Planetary and space exploration: autonomous mapping, soil and rock core sampling and in-situ chemical analysis on surfaces such as the Moon or Mars.

Search and rescue (disaster response): navigating collapsed structures, detecting hazardous gas leaks and locating survivors in areas that are unsafe for human teams.

Mining and geological surveying: subterranean mapping, core sample collection, mineral prospect identification and inspection of structurally unstable mineshafts.

Military and defence reconnaissance: route clearance, forward perimeter surveillance, obstacle mapping and hazardous ordnance inspection.

Agricultural and environmental monitoring: mapping soil moisture and pH across large farms, monitoring crop health, tracking terrain erosion and taking soil samples.

Industrial and hazardous site inspection: monitoring toxic chemical plants, nuclear power facilities and pipeline corridors without putting human operators at risk.

11. CONCLUSION AND FUTURE WORK

The Terrain Exploration and Reconnaissance Integrated Rover System was successfully developed to perform remote terrain exploration and reconnaissance. The rover was able to move in different directions while detecting obstacles using the integrated sensors.

Environmental conditions such as smoke, flame, temperature and humidity were monitored, while the camera provided visual information of the surroundings. The collected sensor data and reconnaissance information could be transmitted through wireless communication to a remote monitoring device.

The Terrain Exploration and Reconnaissance Integrated Rover System provides a reliable approach for remote exploration of difficult and hazardous terrains. By integrating sensors, a camera, wireless communication and motor control on a single ESP32 platform, the rover can detect obstacles, monitor environmental conditions and transmit real-time information to the operator.

The system reduces human risk and improves the efficiency of terrain exploration and reconnaissance operations. Its modular and low-cost design, together with authorised access and selectable operating modes, makes it suitable for disaster response, industrial inspection, environmental monitoring and defence reconnaissance. The project provides a foundation for further development in robotic disaster response, autonomous exploration and surveillance

12. PROGRAM OUTCOMES:

PO1 – Engineering Knowledge: Apply knowledge of mathematics, science, engineering fundamentals, and engineering specialisation to solve complex engineering problems.

PO2 – Problem Analysis: Identify, formulate, review research literature, and analyse complex engineering problems using first principles of mathematics, natural sciences, and engineering sciences.

PO3 – Design/Development of Solutions: Design solutions for complex engineering problems and design system components or processes that meet specified needs, considering public health, safety, cultural, societal, and environmental factors.

PO4 – Conduct Investigations: Use research-based knowledge and methods, including design of experiments, analysis and interpretation of data, and synthesis of information to provide valid conclusions.

PO5 – Modern Tool Usage: Create, select, and apply appropriate techniques, resources, and modern engineering and IT tools, including prediction and modelling, while understanding their limitations.

PO6 – Engineer and Society: Apply reasoning informed by contextual knowledge to assess societal, health, safety, legal, and cultural issues and the responsibilities relevant to professional engineering practice.

PO7 – Environment and Sustainability: Understand the impact of professional engineering solutions in societal and environmental contexts and demonstrate knowledge of sustainable development.



PO8 – Ethics: Apply ethical principles and commit to professional ethics, human values, diversity, and inclusion, and adhere to relevant national and international laws.

PO9 – Individual and Team Work: Function effectively as an individual and as a member or leader in diverse and multidisciplinary teams.

PO10 – Communication: Communicate effectively on complex engineering activities with the engineering community and society, including writing reports, making presentations, and giving and receiving clear instructions.

PO11 – Project Management and Finance: Demonstrate knowledge and understanding of engineering management principles and economic decision-making, and apply them to one's own work and multidisciplinary projects.

13. SDG MAPPING

SDG 3 – Good Health and Well-Being: The proposed rover helps protect human health and safety by allowing operators to inspect dangerous environments remotely. Its obstacle detection and hazard-monitoring sensors can assist during emergency response and reconnaissance operations.

SDG 9 – Industry, Innovation and Infrastructure: The project promotes technological innovation by integrating an ESP32 microcontroller, multiple sensors, a motor driver, a camera, and wireless communication into a single robotic platform. This approach supports the development of affordable and adaptable engineering solutions.

SDG 11 – Sustainable Cities and Communities: The rover can assist in disaster response, building inspection, and emergency reconnaissance by collecting information from potentially unsafe locations, helping response teams assess conditions before entering.

SDG 13 – Climate Action: The system can support reconnaissance and environmental-condition monitoring in areas affected by climate-related emergencies. Its sensors provide information that may assist field assessment, although the rover does not independently prevent or mitigate climate change.

SDG 15 – Life on Land: The rover enables remote exploration of forests, wildlife areas, and difficult terrain. It can help collect environmental information while reducing the need for direct human entry into sensitive locations.

14. REFRENCES

[1] R. Siegwart, I. R. Nourbakhsh and D. Scaramuzza, Introduction to Autonomous Mobile Robots, 2nd ed., MIT Press, 2011.

[2] S. Thrun, W. Burgard and D. Fox, Probabilistic Robotics, MIT Press, 2005.

[3] B. Siciliano and O. Khatib (Eds.), Springer Handbook of Robotics, 2nd ed., Springer, 2016.

[4] X. Wang, H. Shi and H. Yan, “Attributes-Driven Post-Disaster Data Collection and Routing Based on Internet of Robotic Things,” IEEE Internet of Things Journal, 2025.

[5] R. R. Murphy, “Disaster Robotics,” IEEE Transactions on Robotics.

[6] National Institute of Standards and Technology (NIST), Standard Test Methods for Response Robots.

[7] B. Yamauchi, “Frontier-Based Exploration Using Multiple Robots,” Proceedings of the Second International Conference on Autonomous Agents, 1998.

[8] R. R. Murphy, “Trial by Fire: Activities of the Rescue Robots at the World Trade Center,” IEEE Robotics & Automation Magazine, vol. 11, no. 3, pp. 50–61, 2004.

[9] A. Kleiner, C. Dornhege and B. Nebel, “Search and Rescue Robotics,” in Springer Handbook of Robotics, Springer, 2016.

[10] M. Quigley et al., “ROS: An Open-Source Robot Operating System,” ICRA Workshop on Open Source Software, 2009.