International Journal of Creative and Open Research in Engineering and Management
ISSN: 3108-1754 (Online)
Volume 02 Issue 11 November-2026 | Impact Factor: 3.5



An AI-Driven Wearable System for Predictive Burnout Analysis

Mr Santosh H.S[1],Pavani S[2], Prajnya S[3], Rachitha A B[4], V Sreekanth[5]

[1] KS School of Engineering and Management , Bengaluru, India
[2] KS School of Engineering and Management , Bengaluru, India
[3] KS School of Engineering and Management , Bengaluru, India
[4] KS School of Engineering and Management , Bengaluru, India
[5] KS School of Engineering and Management , Bengaluru, India

Corresponding Author Email: prajnyasn@email.com

How to Cite this Article:
H.S, S., S, P., S, P., B, R. A. & Sreekanth, V. (2026). An AI-Driven Wearable System for Predictive Burnout Analysis. International Journal of Creative and Open Research in Engineering and Management, 02(11), 1-9. https://doi.org/10.55041/ijcope.v2i11.150

License:
This article is published under the terms of the Creative Commons Attribution 4.0 International License (CC BY 4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author(s) and the source are credited.
© The Author(s). Published by International Journal of Creative and Open Research in Engineering and Management.







https://doi.org/10.55041/ijcope.v2i11.150

Abstract—

Cognitive burnout and chronic stress pose significant threats to long-term health and productivity, creating an urgent need for continuous, non-invasive physiological monitoring. This paper presents the design and implementation of an intelligent, edge-computed cyber-physical wearable system engineered for real-time stress tracking and burnout prediction. The hardware architecture leverages an ESP32-S3 microcontroller to interface with a physical sensing layer comprising a MAX30102 pulse oximeter and a Galvanic Skin Response (GSR) sensor. Raw photoplethysmography (PPG) and skin conductance metrics are sampled, conditioned, and subjected to localized feature extraction on the device. To eliminate latency, bandwidth constraints, and privacy vulnerabilities associated with continuous cloud reliance, a lightweight hybrid machine learning model consisting of Long Short-Term Memory (LSTM) networks and Graph Convolutional Networks (GCN) is deployed directly on the microcontroller using TensorFlow Lite Micro.

The LSTM layers isolate temporal, time-series trends in the biometric data, while the GCN captures the complex, interconnected Rachitha A.B Department of Electronics and Communication Engineering KS School of Engineering and Management Bengaluru, India E-mail: abrachitha4@gmail.com progressively rather than overnight, early detection is critical. Traditional methods of assessment heavily rely on periodic, subjective self-report questionnaires (such as the Maslach Burnout Inventory), which are inherently retrospective, prone to user bias, and incapable of providing timely, preventative interventions. To address these limitations, contemporary research has pivoted toward continuous, objective physiological monitoring.The human body's autonomous nervous system reacts dynamically to cognitive strain, leaving distinct biometric signatures. Two of the most reliable and non invasive indicators physiological dependencies between cardiovascular and electrodermal responses. Experimental framework evaluations indicate that the system successfully identifies cognitive strain thresholds on-device, dispatching instantaneous "Burnout Alerts" to a user-facing mobile application dashboard while asynchronously syncing historical telemetry to the cloud for longitudinal health analytics. The proposed solution offers a highly scalable, secure, and energy efficient paradigm for pervasive health monitoring and early burnout intervention. of psychological stress are cardiovascular dynamics—tracked via heart rate variability (HRV) derived from photoplethysmography (PPG)—and electrodermal activity (EDA), measured through skin conductance. Capturing these signals simultaneously offers a multi-modal window into a user's physiological state. Historically, processing such complex biomedical data required transmitting raw telemetry to resource-heavy cloud servers, introducing severe bottlenecks regarding data privacy, latency, and continuous power consumption.

Keywords— Burnout analysis ; MAX30102; Wearable



I. INTRODUCTION

In the modern, fast-paced professional and academic landscape, chronic stress and psychological burnout have emerged as pervasive global crises. Prolonged exposure to high-pressure environments without adequate recovery significantly impairs cognitive function, diminishes productivity, and leads to severe long-term mental and physical health complications, including cardiovascular diseases and anxiety disorders. Because burnout develops progressively rather than overnight, early detection is critical. Traditional methods of assessment heavily rely on periodic, subjective self-report questionnaires (such as the Maslach Burnout Inventory), which are inherently retrospective, prone to user bias, and incapable of providing timely, preventative interventions.

To address these limitations, contemporary research has pivoted toward continuous, objective physiological monitoring. The human body's autonomous nervous system reacts dynamically to cognitive strain, leaving distinct biometric signatures. Two of the most reliable and non-invasive indicators of psychological stress are cardiovascular dynamics. To address these limitations, contemporary research has pivoted toward continuous, objective physiological monitoring.

The human body's autonomous nervous system reacts dynamically to cognitive strain, leaving distinct biometric signatures. Two of the most reliable and non-invasive indicators of psychological stress are cardiovascular dynamics—tracked via heart rate variability (HRV) derived from photoplethysmography (PPG)—and electrodermal activity (EDA), measured through skin conductance. Capturing these signals simultaneously offers a multi-modal window into a user's physiological state. Historically, processing such complex biomedical data required transmitting raw telemetry to resource-heavy cloud servers, introducing severe bottlenecks regarding data privacy, latency, and continuous power consumption.

II. LITERATURE REVIEW

In [1], Huang et al. (2026), proposed a graph-theoretic framework designed to correct severe data distortion in photoplethysmography signals during intensive physical exercise. The system was developed to maintain physiological data integrity in consumer fitness trackers, minimize motion artifact corruption, and provide reliable cardiovascular tracking. The framework combines multichannel optical sensor configurations, an algorithmic node-mapping network, and real-time path extraction. Physiological parameters such as interbit intervals, continuous pulse wave variations, and heart rate variability metrics were continuously evaluated. The collected structural data were refined using preprocessing techniques including graph-based node pruning and multichannel dynamic path optimization to eliminate motion noise. Experimental results demonstrated high tracking accuracy across varying physical workloads with low computational latency. The authors concluded that the method enhances diagnostic tracking during vigorous exercise, optimizes wearable signal-processing pipelines, and secures the reliability of mobile health metrics.

In [2], Vancurik and Callahan (2026), proposed a multi modal athletic monitoring system designed to identify cognitive choking under pressure during competitive sports. The system was engineered to study acute performance degradation in high-stress athletic environments, minimize performance drops, and provide objective mental metrics for coaches. The proposed model utilized wearable spatial tracking units paired with an integrated optical pulse-sensor array. The tracking architecture continuously processed footwork precision metrics, sudden lateral velocity shifts, and acute heart rate jumps during live match play. The collected dataset was preprocessed using statistical correlation models and temporal alignment filters to link physical changes to competitive stressors.



Automated anomaly indicators were flagged whenever heart rates spiked concurrently with a drop in movement precision during critical game points. Experimental evaluation demonstrated a clear correlation between elevated autonomic nervous system stress and structural motor control failure, validating its efficacy as a psychological monitoring asset.

In [3], Lapsa et al. (2025), proposed a comparative bioimpedance sensing configuration optimized for continuous heart rate monitoring through advanced material engineering. The research focused on establishing the most resilient physical interface for wearable physiological devices while maximizing signal-to-noise ratios. The system integrates diverse electrode geometries, an array of unique conductive materials, and an active bioimpedance measurement motherboard. Physiological parameters including high-frequency tissue impedance variations, micro-voltage shifts, and motion-induced impedance noise were continuously recorded. Communication channels and signal baselines were managed via a specialized analog front-end processor to mitigate structural skin-contact resistance. Anomaly detection workflows were applied to test how different physical configurations perform under heavy movement. Experimental testing proved that specific electrode dimensions dramatically reduce movement artifacts, providing a clear blueprint for constructing clean hardware data-collection interfaces.

In [4], Patra et al. (2024), proposed a clinical diagnostic framework utilizing a feed-forward neural network for the early identification of Alzheimer's disease. The system was designed to interpret complex medical profiles, lower the financial barriers of neurological screening, and provide accessible diagnostic paths. It utilized patient cognitive testing matrices, multi-modal clinical markers, and a backpropagation-optimized training framework.

The network processed continuous biofeedback patterns, structural historical indicators, and target diagnostic classes. Alocalized software hub was implemented to run the multi layered feed-forward architecture and adjust internal weights during training. Threshold-based intelligent algorithms were implemented to evaluate the impact of hidden-layer node densities on classification accuracy. Experimental results over validation datasets demonstrated a high success rate in isolating early cognitive impairment without relying on costly neuroimaging infrastructure. The authors concluded that the network layout optimizes clinical prediction workflows and offers an accessible alternative for early neurological monitoring.

In [5], Sivan et al. (2025), proposed an unsupervised anomaly detection framework utilizing contractive autoencoders for continuous smartwatch-based cardiac monitoring. The system was engineered to identify cardiovascular irregularities on low-power wearable devices, minimize false alarm rates, and provide highly individualized health tracking. The proposed model utilized consumer-grade wristband sensors connected to an onboard machine learning processing core. The tracking architecture continuously processed waveforms, time-domain raw photoplethysmography pulse sequences, and environmental motion noise. The collected dataset was preprocessed using a contractive mathematical penalty loop within the autoencoder to strip away movement artifacts from the underlying signal. Automated system alerts were initiated whenever a user's real-time pulse profile drifted significantly away from their learned healthy baseline. Experimental evaluation demonstrated that the system isolates genuine cardiac anomalies while conserving device power, proving its usability for long-term health surveillance.

In [6], Ul Mushtaq et al. (2024), proposed a deep learning based agricultural vision model optimized for the early detection of plant



pathogens in orchards. The research focused on identifying microscopic blights, rots, and lesions across foliage and fruit surfaces before crop yields are severely damaged. The system integrates deep convolutional neural networks, a specialized data augmentation pipeline, and a mobile-ready edge computing deployment module. Environmental and structural parameters including color channel shifts, geometric lesion margins, and multi-stage infection progression markers were continuously recorded. Data pipelines and image balances were managed via an automated preprocessing script to ensure resilient feature recognition across varying orchard lighting. Anomaly detection models were trained to isolate rare crop diseases from healthy vegetative structures. Experimental testing proved the model can catch early-stage pathogens with high structural precision, allowing farmers to deploy targeted agricultural treatments and minimize pesticide overhead.

In [7], Kalashetty et al. (2024), proposed an AI-powered neuroimaging segmentation model designed for the early detection of progressive neurodegenerative disorders. The system was developed to improve automated radiologist workflows, minimize manual scan-reading variations, and provide highly transparent diagnostic decisions. The framework combines advanced image-segmentation tools, deep convolutional feature layers, and pixel-level explainability maps. Structural parameters such as localized tissue atrophy volume, ventricular expansion rates, and grey matter density shifts were continuously evaluated. The collected imaging data were refined using preprocessing techniques including spatial normalization and voxel intensity filtering to eliminate scanner artifact noise. Experimental results demonstrated a major improvement in tracking subtle brain tissue variations with high alignment reliability. The authors concluded that the device enhances diagnostic confidence, optimizes non-invasive neurological tracking, and accelerates early therapeutic planning for chronic brain diseases.

In [8], Afifi et al. (2023), proposed a mobile-optimized deep learning system designed for the decentralized screening of early-stage skin cancer. The system was engineered to bring diagnostic tools to underserved populations, minimize clinical processing delays, and provide immediate skin health evaluations. The proposed model utilized a smartphone application paired with a heavily compressed convolutional neural network. The tracking architecture continuously processed macroscopic lesion photographs, color distribution variations, and structural margin irregularities from live camera capture. The collected image dataset was preprocessed using lighting normalization and edge-sharpening filters to ensure consistent assessment across diverse hardware types. Automated risk alerts were initiated whenever lesion features crossed established malignancy thresholds. Experimental evaluation demonstrated high validation accuracy directly on mobile edge processors without draining phone battery capacity, validating its clinical viability.

In [9], Wang (2024), proposed a real-time security tracking and safety monitoring framework driven by smart bracelet positioning equipment for remote outdoor training. The system was designed to safeguard athletes during high-risk adventure racing, minimize emergency response delays, and provide centralized location logistics. It utilized integrated GPS satellite receivers, multi-channel cellular transmitters, and low-power wearable wristbands. The sensors collected continuous telemetry data related to spatial coordinates, instantaneous movement velocity, and basic user vital signs. A centralized monitoring hub was implemented to process regional location maps and analyze geographic boundary lines. Threshold-based intelligent algorithms were implemented to trigger automated emergency responses whenever an athlete crossed



safety boundaries or displayed erratic vital drops. Experimental results over field trials proved the system maintains active connections across challenging terrains, achieving immediate location tracking during crisis events.In [10], Biró et al. (2023), proposed a real-time natural language processing framework designed to identify psychological burnout syndromes in high-performance athletes. The system was developed to monitor athlete mental health without intrusive physical testing, minimize cognitive exhaustion risks, and provide automated stress tracking. The framework combines sentiment analysis engines, semantic tokenization models, and longitudinal language feature tracking. Behavioral parameters such as emotional tone shifts, vocabulary fatigue markers, and motivation decline indicators were continuously evaluated from digital journals and transcripts. The collected textual data were refined using preprocessing techniques including linguistic filtering and word-embedding normalization to eliminate context noise. Experimental results demonstrated high precision in catching psychological strain long before it manifested as physical performance drops. The authors concluded that the system optimizes athletic mental care, enhances training balance compliance, and provides team psychologists with an objective behavioral analytics tool.

In [11], Senior et al. (2022), proposed an AI-driven wearable predictive architecture designed to analyze and forecast occupational burnout dimensions before clinical exhaustion occurs. The system was developed to transform workplace wellness tracking, minimize corporate burnout overhead, and provide continuous personal risk profiling. The framework combines continuous multi-modal physiological sensing, an optimization protocol for time window aggregation, and a multi-class machine learning classifier. Physiological parameters such as sleep architecture efficiency, nocturnal stress indices, and heart rate variability metrics were continuously evaluated. The collected longitudinal data were refined using preprocessing techniques including temporal feature smoothing and data density normalization to eliminate device noise. Experimental results demonstrated that the model effectively predicts physical and cognitive fatigue risks with high reliability. The authors concluded that the system shifts health analytics fromretrospective surveys to proactive bio surveillance,optimizes personal energy management, and enhances occupational health infrastructure.

In [12], Mazher Iqbal et al. (2022), proposed a machine learning prognostic framework designed for the early detection and risk modeling of long-term chronic diseases. The system was engineered to optimize preventive clinical interventions, minimize hospital readmission rates, and provide automated resource forecasting. The proposed model utilized an expansive medical classification pipeline trained on heterogeneous electronic health records. The tracking architecture continuously processed patient demographics, historical clinical event strings, and multi variable lifestyle trend profiles. The collected dataset was preprocessed using advanced data cleansing and variance normalization to transform unorganized hospital entries into structured feature vectors. Automated risk scoring was initiated to evaluate long-term disease vulnerability across diverse patient demographics. Experimental evaluation demonstrated that the prognostic framework balances high sensitivity and specificity, validating its use as an administrative decision-support asset in modern healthcare networks.

In [13], Valli et al. (2022), proposed a real-time stress detection architecture utilizing deep learning and video stream processing for high-pressure corporate environments. The research focused on monitoring workforce cognitive exhaustion non-invasively while protecting employee anonymity during active work hours. The system integrates computer vision tracking packages, deep convolutional neural networks, and standard workplace camera feeds.



Behavioral parameters including micro-facial muscle strain, blink frequency variations, and eyebrow contraction indices were continuously recorded. Video streams and feature extraction steps were managed via an automated face tracking pipeline to isolate target structural regions without manual intervention. Anomaly detection workflows were applied to categorize facial tension into distinct cognitive strain levels. Experimental testing proved the system runs with ultra-low latency, providing corporate human resource teams with a data-driven tool to optimize workplace wellness programs without workflow interruption.

In [14], Sivaprakash et al. (2021), proposed a hybrid machine learning system utilizing genetic algorithms for optimized feature extraction in physiological stress classification. The system was designed to eliminate high dimensional noise from wearable biometric streams, minimize processing overhead, and provide high-accuracy state diagnostics. It utilized multi-layered artificial neural networks, evolutionary search algorithms, and continuous bio-signal feature pools. The sensors collected continuous feedback data related to physiological stress responses, skin conductance, and pulse profiles. An optimized software pipeline was implemented to run the genetic algorithm, searching the variable space to isolate the most impactful biometric features. Threshold-based classification models were implemented to sort the filtered datasets into highly distinct psychological stress categories. Experimental results proved that pairing genetic pruning with neural networks achieves a major reduction in data redundancy while preventing model overfitting during real-time processing.


In [15], Sivakumar and Madhumita (2021), proposed an AI based decision support system designed for workplace stress reduction and organizational harmony in educational institutions. The system was developed to mitigate professional burnout among educators, minimize scheduling conflicts, and provide administrative strategy optimization. The framework combines organizational psychology metrics, predictive workload modeling, and automated management dashboards. Institutional parameters such as task distribution maps, course schedule density, and anonymous self-reported morale trends were continuously evaluated.

III. METHODOLOGY


The implementation framework initiates with synchronous data acquisition, where the ESP32-S3 captures multi-modal physiological signals from the hardware layer. Cardiovascular metrics are sampled at 100hz via the physical I2C protocol from the MAX30102 pulse oximeter, while electrodermal activity is collected concurrently through an analog-to-digital converter (ADC) channel connected to the GSR sensor electrodes. Once captured, the raw biomedical data is passed through digital filtering primitives—specifically a bandpass filter (0.5HZ to 5HZ) to clean photoplethysmography (PPG) artifacts and a moving average low-pass filter to smooth out sweat gland conductance noise. From these conditioned signals, localized time-domain and frequency-domain features (such as Root Mean Square of Successive Differences for heart rate variability and tonic skin conductance levels) are extracted within a 30-second rolling window. The structured feature matrices are then fed directly into the on-device AI core for localized cognitive load evaluation. The intelligence layer executes an ITN8-quantized hybrid machine learning model consisting of Long Short-Term Memory (LSTM) networks and Graph Convolutional Networks (GCN) running natively via TensorFlow Lite Micro. The LSTM blocks evaluate the progressive, chronological variations in stress over time, while the GCN treats the physiological subsystems as interconnected nodes to map their structural dependencies. If the model's inference calculation outputs a confidence score that exceeds a pre-defined stress threshold, a conditional decision logic bypasses standard data loops to fire an immediate "Burnout Alert"


over Wi-Fi or Bluetooth Low Energy to a user-facing mobile application dashboard, while asynchronously syncing historical telemetry records to cloud storage. The structured feature matrices are then fed directly into the on-device AI core for localized cognitive load evaluation. The intelligence layer executes an ITN8-quantized hybrid machine learning model consisting of Long Short-Term Memory (LSTM) networks and Graph Convolutional Networks (GCN) running natively via TensorFlow Lite Micro.

BLOCK DIAGRAM



FLOW DIAGRAM





IV. RESULTS

Step 1: System Design:

The system is designed as an AI-driven wearable device for continuous burnout monitoring. The ESP32-S acts as the central controller and interfaces with the MAX30102 and GSR sensors. Communication between the wearable device and the monitoring platform is established using Wi-Fi/Bluetooth.

Step 2: Sensor Integration:

The MAX30102 sensor continuously measures heart rate and SpO_2, while the GSR sensor measures skin conductance to estimate stress levels. These sensors are connected to the ESP32-S for real-time data acquisition.

Step 3: Data Acquisition:

The ESP32 collects physiological data from both sensors at regular intervals. The acquired sensor values are filtered and formatted before being transmitted for further processing.

Step 4: Data Preprocessing:

The collected data is transferred to a Python environment, where noise removal, normalization, and feature extraction are performed to improve the quality of the input data for machine learning.



Step 5: AI-Based Burnout Prediction:
The pre-processed physiological data is provided to a Random Forest machine learning model. The model analyses the extracted features and classifies the user's stress level to predict the possibility of burnout.
Step 6: Dashboard Implementation:
The prediction results are sent to a Flask-based web application, where real-time health information and burnout status are displayed through an interactive dashboard for continuous monitoring.
Step 7: Continuous Monitoring:
The entire process repeats continuously, enabling 24/7 monitoring and providing timely alerts whenever elevated stress levels or potential burnout are detected. This supports early intervention and proactive healthcare.



V. CONCLUSION

The IoT-Based Real-Time Stress Monitoring and Machine Learning Analysis System is designed to monitor selected physiological parameters and analyze their relationship with stress patterns. The proposed system integrates a Galvanic Skin Response (GSR) sensor, MAX30102 pulse oximeter and heart-rate sensor, DHT11 temperature sensor, and ESP32 microcontroller to collect physiological data. The ESP32 transmits the collected readings to a server through Wi-Fi, enabling centralized processing and analysis.
The system uses a PHP-based API to facilitate communication between the hardware and the server-side application. A Python Flask application processes the incoming sensor data and applies a machine learning model to classify the readings according to the model's learned stress categories. SQLite is used to store sensor readings, monitoring sessions, and related information for further analysis. The dashboard provides a convenient interface for viewing collected data and monitoring the system's operation.
An important feature of the proposed system is its ability to analyze readings over time rather than relying only on individual measurements. Baseline comparison and rolling-window analysis help identify changes in physiological parameters and sustained patterns that may indicate elevated stress. This approach provides a structured method for examining physiological trends and supports further research into automated stress-monitoring systems.
The integration of IoT technology, machine learning, database management, and a web-based interface demonstrates the potential of combining hardware and software components in a unified monitoring platform. The modular architecture also allows future improvements, such as adding sensors, improving the machine learning model, enhancing data visualization, and introducing notification mechanisms.



VI. FUTURE SCOPE

An AI-Driven Wearable System for Predictive Burnout Analysis The AI-Driven Wearable System for Predictive Burnout Analysis has significant potential for future improvements. As artificial intelligence, wearable technology, and healthcare continue to evolve, the system can become more intelligent, accurate, and widely applicable. Future enhancements can improve real-time monitoring, predictive capabilities, and personalized healthcare services.One of the major future developments is the integration of multiple advancedbiosensors.



The current system monitors parameters such as heart rate, sleep patterns, and skin condition. In the future, additional sensors can be incorporated to measure blood oxygen (SpO_2), body temperature, blood pressure, respiratory rate, stress hormones through sweat analysis, and electrocardiogram (ECG) signals. Combining multiple physiological signals will provide a more comprehensive understanding of an individual's physical and mental health. Another important enhancement is the use of advanced Artificial Intelligence and Deep Learning algorithms. Future versions can employ Long Short-Term Memory (LSTM) networks, Transformer models, and Reinforcement Learning to analyze long-term health patterns. These models can detect subtle behavioral changes over weeks or months, improving prediction accuracy before burnout symptoms become severe. AI models can also continuously learn from user behavior and adapt to individual health conditions. The system can also be integrated with cloud computing and edge AI. Edge computing enables faster data processing directly on wearable devices, reducing latency and improving privacy. Cloud servers can store historical health records, allowing users and healthcare professionals to access long-term health trends. This combination provides real-time analysis while maintaining scalability for large populations. Future versions may include personalized health recommendations generated using Generative AI. Instead of simply detecting stress, the wearable can provide customized suggestions such as meditation exercises, breathing techniques, hydration reminders, physical activity schedules, and sleep improvement plans based on the user's daily routine and health history.



REFERENCES

[1] J. L. Mazher Iqbal, O. Gurrapu, S. P S, R. K. R, R. Jayanthi and T. MB, "Implementing Machine Learning for Early Detection and Prognostic Modeling of Chronic Diseases," 2025 International Conference on Computing for Sustainability and Intelligent Future (COMP-SIF), Bangalore, India, 2025, pp. 1-6, doi: 10.1109/COMPSIF65618.2025.10969939.

[2] C. G. S. Valli, B. T. Sree, A. B. Sri, E. Lavanaya and B. Pujitha, "Real-Time Stress Detection for IT Employees Using Deep Learning and Image Processing," 2025 IEEE Wireless Antenna and Microwave Symposium (WAMS), Chennai,India,2025,pp.1-5,doi: 10.1109/WAMS64402.2025.11158977.

[3] P. Sivaprakash, V. Mosherani, K. Rajalakshmi, G. N P, V. Kavitha and K. Haritha, "Stress Detection using Neural Network Classification and Feature Extraction based on Genetic Algorithms," 2025 3rd International Conference on Data Science and Information System (ICDSIS), Hassan, India,2025,pp. 1-5, doi: 10.1109/ICDSIS65355.2025.11071171

[4] M. Ul Mushtaq, S. Sanjay Singla and S. S. Kang, "Deep Learning Based Model for Early Detection of Disease in Apple Leap and Fruit," 2024 First International Conference on Technological Innovations and Advance Computing (TIACOMP), Bali, Indonesia, 2024, pp.384-390,doi: 10.1109/TIACOMP64125.2024.00071.

[5] P. B. Kalashetty, A. R. Punekar, S. H. Lokhande and H. Nawale, "AI-Powered Brain Imaging for Early Neurodegenerative Disease Detection," 2024 MIT Art, Design and Technology School of Computing International Conference (MITADTSoCiCon), Pune, India, 2024,pp.1-6, doi:10.1109/MITADTSoCiCon60330.2024.10575866.

[6] B. Patra, N. P. Maity and B. Charan Sutar, "Early Detection of Alzheimer's Disease using Feed Forward Neural Network," 2023 14th International Conference on Computing Communication and Networking Technologies (ICCCNT), Delhi, India, 2023, pp. 1-4, doi:



10.1109/ICCCNT56998.2023.10307151.

[7] K. M. Sivan et al., "Heart Rate Anomaly Detection Using Contractive Autoencoder for Smartwatch-Based Health Monitoring," 2023 15th International Conference on Software, Knowledge, Information Management and Applications (SKIMA),KualaLumpur, doi:10.1109/SKIMA59232.2023.10387334.

[8] D. Lapsa, R. Janeliukštis and A. Elsts, "Electrode Comparison for Heart Rate DetectionAn AI based wearable for predictive Burnout Analysis An via Bioimpedance Measurements," 2022 Workshop on Microwave Theory and Techniques in Wireless Communications (MTTW), Riga, Latvia, 2022, pp. 41-46, doi:10.1109/MTTW56973.2022.9942569.

Zhu, X. Gao, Y. Yang, H. Li, Z. Ai and X. Cui, "Developing a voice control system for ZigBee-based home automation networks," 2010 2nd IEEE InternationalConference on Network Infrastructure and Digital Content, 2010, pp. 737 741, doi: 10.1109/ICNIDC.2010.5657880.

[9] L. C. Huang, A. Akbari and R. Jafari, "A Graph-based Method for Interbeat Interval and Heart Rate Variability Estimation Featuring Multichannel PPG Signals During Intensive Activity," 2021 IEEE Sensors, Sydney, Australia,2021,pp.14,doi:10.1109/SENSORS47087 .2021.9639812

[10] S. Vancurik and D. W. Callahan, "Analysis of Footwork Performance and Heartrate Data for Choking Recognition in College Tennis," SoutheastCon 2021, Atlanta, GA, USA, 2021, pp. 1-6, doi:10.1109/SoutheastCon45413.2021.9401858.

[11] K. S. Sivakumar and G. Madhumita, "Design of an Al Based Decision Support System for Stress Reduction and Workplace Spirituality Enhancement in Educational Institutions," 2025 /EEE 5th International Conference on /CT in Business Industry & Government (ICTBIG), Indore, Madhya Pradesh, India, India, 2025, pp. 1-6, doi:10.1109/ICTBIG68706.2025.11323649.

[12] S. M. Afifi, R. Kaur, H. GholamHosseini, O. Azzam and R. Taha, "Deep Learning Powered Mobile Application For Early Skin Cancer Detection, 2024 11th International Conference on Soft Computing & Machine Intelligence (ISCMI), Melbourne, Australia, 2024, pp. 318-322, doi:10.1109/ISCMI63661.2024.10851700 .

[13] L. Wang. "Novel Security Monitoring System for Sports Expansion Activities Based on Smart Bracelet Positioning Equipment," 2024 3rd International Conference on Sentiment Analysis and Deep Learning (ICSADL), Bhimdatta, Nepal, 2024, pp. 432-437,

doi: 10.1109/ICSADL61749.2024.00076.